

KAT2 ANTENNA TUNER MANUAL ERRATA (D-1)

**PLEASE MAKE THE FOLLOWING CHANGES TO THE MANUAL BEFORE
PROCEEDING TO ENSURE THAT THE KAT2 FUNCTIONS CORRECTLY**

Page 5, third assembly step: Add the following at the end of this step: "T1 must be wound exactly as shown, with leads 1 and 3 emerging from the back side of the core and leads 2 and 4 from the front side."

Page 13, first assembly step: If you have the KIO2 serial interface option installed, you should disconnect it from the K2 control board until KAT2 testing is complete. The KAT2 and KIO2 can then both be connected to the control board using the small junction board supplied with the KIO2.

Page 18, first assembly step: Add the following at the end of this step: "Make sure that the ground lug on the receive antenna jack (part of the 160m option) is rotated down towards the K2's RF board."

KAT2 ANTENNA TUNER MANUAL ERRATA (D-1)

**PLEASE MAKE THE FOLLOWING CHANGES TO THE MANUAL BEFORE
PROCEEDING TO ENSURE THAT THE KAT2 FUNCTIONS CORRECTLY**

Page 5, third assembly step: Add the following at the end of this step: "T1 must be wound exactly as shown, with leads 1 and 3 emerging from the back side of the core and leads 2 and 4 from the front side."

Page 13, first assembly step: If you have the KIO2 serial interface option installed, you should disconnect it from the K2 control board until KAT2 testing is complete. The KAT2 and KIO2 can then both be connected to the control board using the small junction board supplied with the KIO2.

Page 18, first assembly step: Add the following at the end of this step: "Make sure that the ground lug on the receive antenna jack (part of the 160m option) is rotated down towards the K2's RF board."